

CS108 is the best in class read range UHF RFID Sled Reader in the market. It works with all Android phones, iPhones and Tablets. It enables fast inventory of items in business processes where fixed reader class performance is required in a portable device. CS108 is used globally in many mission critical government, industrial and commercial applications.



## PRODUCT FEATURES:

### Read Range:

Best in class read range:

- Up to 18 meters with Linear Polarized.
- Up to 15 meters with Circular Polarized Antenna. (tag and environment dependent)

### Specific Frequency Bands Available For Your Count

#### Choice of:

- Vertically linear polarized
- Horizontally linear polarized
- Circular polarized.

### Ruggedized design

Drop test 1.2 meters on 6 surfaces, IP54 rated

### Optional 2d Barcode Scanner Module

### Works with all Android Phones or iPhones

Android API, iPhone API, Linux API, Windows API

**Read RFID tags and barcodes with one device.**

**Use any size device and operating system.**


**Mounting options for tablets or thick enterprise devices.**

**Read passive RFID temperature sensor tags.**



**DEMO APP** download





Order Code for Frequency Regulations: CS108-V/H/C-2D-N  
 N=1 865-868 MHz (Europe) & 865-867 MHz (India)-HFL  
 N=2 902-928 MHz US, Canada & Mexico-HFL  
 N=2 AS for 920-926 MHz, Australia only-HFL  
 N=2 NZ for 921.5-928 MHz, New Zealand only-HFL  
 N=2 OFCA for 920-925 MHz, Hong Kong only-HFL  
 N=2 RW for 902-928 MHz, Rest of the world that are subset of this band: e.g. Philippine, Brazil, Peru, Uruguay, Singapore, Thailand, etc.  
 N=4 922-928 MHz, Taiwan  
 N=7 920-925 MHz, China, Malaysia, etc.  
 N=8 916.7-920.9 MHz, Japan  
 N=9 915-921 MHz, Europe Upper Band  
 (V for vertically linear polarized, H for horizontally linear polarized, C for circular polarized, 2D means with 2D Barcode options, HFL: Hopping Frequencies Locked)



Optional 2D Barcode Scanner



Dual Battery Charger



Extra Battery

### Dimensions and weight

Length: 161 mm (6.34 in); Width: 90 mm (3.54 in); Height: 161 mm (6.34 in); Weight: 639 g (without 2D Barcode Module).

### Read Range

Best in Class Read Range:  
 -Up to 20 meters with Linear Polarized Antenna (tag and environment dependent)  
 -Up to 15 meters with Circular Polarized Antenna (tag and environment dependent)

### Protocol:

ISO18000-6C, EPC UHF Class 1 Gen 2, Dense Reader Mode available (Class 3 Gen 2 compliant)

### Frequency Range:

One of the following: 865-868 MHz, 865-867 MHz, 902-928 MHz, 922-928 MHz, 920-925 MHz, 915-922 MHz, 915-921 MHz

### Tag Information:

All banks any sizes (e.g. 240 bits bank1, 512 bits bank3), Per "Tag Read" RSSI value

### Barcode Scanner

2D module option available

### Antenna Polarization

Vertically linear / Horizontally linear / Circular polarized

### Environment

Operating Temp: -20° C to 55° C (-4° F to 131° F)  
 Storage Temp: -40° C to 75° C (-40° F to 167° F)

### Ruggedized Design

Drop test 1.2 meters on the six sides; IP54

### Interfaces

Android Phone, iPhone, Windows PC, Linux PC

### Battery Capacity

3,400 mAh, field replaceable  
 Option: extra battery (CS1088); external charger (CS108C)

### Source Code Samples

Read / Write tag, Tag inventory / ranging / search / authentication / association / commissioning, Barcode scanning, database manipulation, wireless network transfer, server side driver, etc.