

ZT400 Series RFID Industrial Printers/Encoders

Proven durability and versatility with UHF RFID encoding

Pairing rugged quality with UHF RFID capabilities, the ZT400 Series RFID printers/encoders help keep your critical operations running efficiently. Known as price-performance leaders in RFID labeling, the ZT400 Series offers a factory- or field-installable UHF RFID encoder to support a broad range of applications across several industries. See printer status at a glance and manage settings quickly-including RFID-using the large color touch display. Featuring Zebra's Print DNA suite of applications, utilities and developer tools—all powered by Link-OS®—these printers are easy to integrate, manage and maintain from any location around the globe. Optimized to accurately and efficiently print and encode labels for today's item-level tracking applications, the ZT400 Series RFID printers give you greater tracking abilities, deeper visibility and enterprise insights in an ever-competitive business environment.



Versatile to meet your evolving needs

Configure your way with multiple connectivity options

The ZT400 comes standard with Ethernet, Serial, USB, dual USB Host and Bluetooth 4.1. Add the optional dual-band wireless card with 802.11ac Wi-Fi and Bluetooth for blazing fast and reliable wireless connections.

Built to handle a wide range of applications including high-resolution

You can count on the ZT400 Series to print a variety of different label formats on a variety of different media types. When RFID-enabled, the 4-inch ZT411 and 6-inch ZT421 can print and encode labels as small as 0.6 in./16 mm. And, the ZT411 can print up to 600 dpi for extremely crisp resolution. The ZT411 RFID, available in an on-metal version, is the only dedicated option for printing and encoding on-metal tags and labels.

Dual USB Host ports for added flexibility

Dual USB Host ports allow you to directly connect a wide range of USB device types. Use a memory stick to replicate firmware, files and configurations, or easily print and transfer formats. Simplify data entry by simultaneously connecting a scanner and keyboard — with two host ports, there's no need to plug and unplug peripherals.

Designed to evolve with your needs

You can customize the ZT400 Series with a range of media handling options that can be easily installed in minutes. Two open media slots accommodate additional communication options. And, the open architecture, robust processing power and memory can support firmware upgrades and new Print DNA tools for years to come.

Effortless to integrate and operate

Large color touch display makes operation a snap

It's easy to set up and use the ZT400 with its intuitive icon-based interface, including managing RFID settings. The 4.3-inch full-color touch display allows you to quickly navigate printer settings and create frequently used shortcuts. See color-coded alerts from a distance when the printer is paused or in an error state, so you instantly know what the printer needs to stay up and running.

Backward compatible with virtually any existing printer

Whether you are currently using a Zebra RZ Series printer/encoder or competitive printer, you can use the same label formats and applications with the ZT400. Support for both EPL and ZPL makes it easy to mlgrate from another Zebra desktop printer. With Virtual Devices, part of Zebra's Print DNA, the ZT400 can use languages normally associated with other printer brands.



Keep your critical operations running efficiently with the ZT400 Series RFID Industrial Printers/Encoders.

ZT400 Series RFID

Industrial Printers/Encoders

PRODUCT SPEC SHEET

ZT400 SERIES RFID INDUSTRIAL PRINTERS/ENCODERS

Print and encode with ease

Adaptive encoding technology allows for excellent media flexibility and simple RFID calibration, eliminating complex placement guidelines. And, Zebra has globally certified its RFID technology on six continents to support deployments across complex, multinational supply chains.

Easy media and ribbon loading

The side-loading supplies path makes loading simpler, faster and more intuitive — even for new users. The color-coded media path guides you on how to thread the media and ribbon through the printer, while lighted paths make it easy to see, even in poorly lit environments.

Space-saving design for an easier fit

Constructed using a bi-fold door, these printers are designed to easily fit in space-constrained environments. ENERGY STAR® qualified, they save you money throughout their lifecycle.

Direct connection to your Industrial Ethernet network

With the Network Connect option, you can connect ZT400 printers directly to your Industrial Ethernet network without any additional equipment. This eliminates vulnerability points, improves security and saves man-hours in setup, management and troubleshooting.

Pair devices and access information at a touch

With the Print Touch app, you can pair ZT400 Series printers to NFC-enabled devices with a simple tap. Dynamic QR codes give you immediate access to the data you need, including Zebra how-to videos and product support.

Easy to Manage

Zebra Print DNA — transforming printers from the inside

The printer hardware is just the start of what you need to maximize the value of your printers. The ZT400 Series is powered by Link-OS, Zebra's robust printer operating system, and Print DNA, a combination of productivity, management, development and visibility tools. The result is a superior printing experience through better performance, simplified remote manageability and easier integration.

Easily manage all your printers — all from a single location

With our comprehensive and flexible remote management tools, you can maintain, secure and troubleshoot printers simply and easily, from anywhere, at anytime. With Printer Profile Manager Enterprise, a Print DNA option, you can manage one printer, a group of specific printers or all your printers anywhere in the world. This browser-based solution lets you instantly discover every Link-OS printer on your network — there's no need to manually track down, configure or troubleshoot printers. In addition to optional enterprise remote management tools, we offer a full suite of complimentary deployment utilities to simplify initial setup and configuration.

Seamless integration with your device management system

Get the simplicity of a single pane of glass to manage all your Zebra devices and printers — including the ZT400 Series RFID. With Print DNA's MDM Connectors, you can easily integrate networked ZT400 printers into your existing AirWatch or SOTI MobiControl device management system.

Performance You Can Count On

On-metal RFID option enables metal asset tagging

Zebra offers an optional version of the ZT411 for on-metal RFID tagging. This solution enables users to print and encode on-metal RFID labels such as Silverline that are designed to work on a variety of surfaces including IT assets, tools, equipment, returnable containers and other challenging surfaces. The ZT411 RFID On-metal Solution gives you greater flexibility that is globally available—including simple-to-install, field-upgradeable technology and 300 dpi print quality.

Rugged durability for demanding applications

You can count on the ZT400 to serve your business for years. Its durable metal frame holds up in the most demanding environments, while a long life coating protects the printheads when printing in direct thermal mode, reducing the need to replace printheads. Ensure optimal print quality with the printhead element out detection feature. Every detail has been carefully designed and tested to deliver maximum uptime over the printer's life.

Consistently exceptional Zebra Certified Supplies

Printing supplies can impact everything from printhead lifespan to operational efficiency. That's why we design, produce and rigorously pretest our own line of thermal printing supplies to ensure consistent, optimized performance in your Zebra printer. We offer the widest selection of in-stock RFID labels and tags for general purpose, advanced and specialty use applications, in a variety of sizes and materials, using inlays from leading manufacturers. For our On-metal RFID Tagging Solution, we offer four types of Confidex Silverline labels to support any size and application.

Maximize uptime, business operations and printer visibility with services

You invest in Zebra printers to boost the efficiency of your critical operations. Now, you can ensure predictable performance and eliminate unbudgeted repair expenses with Zebra OneCare. You get unmatched technical support direct from Zebra, as well as comprehensive repair services, including accidental damage and defined repair turn-around times. And Zebra's Support and Visibility Services provide the real-time insight into printer operational information you need to increase printer availability and optimize utilization within your workflows.

ZT400 Series RFID Specifications

- Integrated RFID system is user-upgradable in the field
- Optional field-upgradeable on-metal version available (ZT411 only)
- Prints and encodes tags with a minimum pitch of 0.6 in./16 mm
- Supports tags compatible with: UHF EPC Gen 2 V2, ISO/IEC 18000-63 and RAIN RFID protocols
- Compliant with Global RFID radio to support multinational deployments
- Automatically eliminate complex RFID placement guidelines with adaptive encoding technology
- Variable inlay placement supports a range of inlay positions for maximum medla flexibility
- Track performance with RFID job-monitoring tools
- · Support for industry standard multi-vendor chip-based serialization (MCS)
- Supports block permalocking of user memory compatible with ATA Spec 2000
- Integrated ThingMagic® RFID reader/encoder

Standard Features

- · Print Methods: Thermal transfer and direct thermal printing
- Construction: Meta! frame and bi-fo!d metal media cover with enlarged clear viewing window
- · Side-loading supplies path for simplified media and ribbon loading
- Thin film printhead with E3™ Element Energy™ Equalizer for superior print quality
- Communications: USB 2.0, high-speed, RS-232 Serial, 10/100 Ethernet, Bluetooth 4.1, Dual USB Host
- 4.3-inch color touch display with intuitive menu for quick operation and settings management
- · Bi-colored status LEDs for quick printer status
- ENERGY STAR® qualified

Physical Character	istics
Dimensions (closed)	ZT411: 19.5 in. L x 10.6 in. W x 12.75 in. H 495 mm L x 269 mm W x 324 mm H ZT421: 19.5 in. L x 13.25 in. W x 12.75 H 495 mm L x 336 mm W x 324 mm H
Weight	ZT411: 36 lbs./16.33 kg ZT421: 40 lbs./18.14 kg
Printer Specification	ns
Resolution	203 dpi/8 dots per mm 300 dpi/12 dots per mm (optional) 600 dpi/24 dots per mm (optional fo: ZT411 only)
Memory	256 MB SDRAM memory 512 MB on-board linear Flash memory
Maximum Print Width	ZT411: 4.09 in./104 mm ZT421: 6.6 in./168 mm
Maximum Print Speed	ZT411: 14 ips/356 mm per second ZT421: 12 ips/305 mm per second
Media Sensors	Adjustable dualmedia sensors: transmissive and reflective
Print Length	ZT411 • 203 dpt: 157 in./3988 mm • 300 dpt: 73 ln./1854 mm • 600 dpt: 39 in./991 mm
	ZT421 • 203 dpi: 102 in./2591 m:n • 300 dpi: 45 in./1143 mm

Maximum Media Width	ZT411 • 1.00 in./25.4 mm to 4.5 in./114 mm tear/cutter • 1.00 in./25.4 mm to 4.25 in./108 mm peel/rewind
	ZT421 • 2.00 ln./51 mm to 7.0 in./178 mm teadcutter • 2.00 ln./51 mm to 6.75 in./171 mm peel/rewind
Maximum Media Roll Size	8.0 in./203 mm 0.D. on a 3 in./76 mm I.D. core
Thickness	0.0023 in./0.058 mm to 0.010 ln./0.25 mm On-metal option: up to 0.059 in./1.5 mm
Media Types	Continuous, die-cut, notch, black-mark
Ribbon Characteri	stics
Standard Length	1476 ft./45C M
Width	ZT411: 2.00 in./51 mm to 4.33 ln./110 mm ZT421: 2.00 in./51 mm to 6.85 ln./174 mm
Core I.D.	1.0 in./25 mm
Environmental	
Operating Temperature	Thermal transfer: 40° F to 104° F/5° C to 40° C Direct thermal: 32° F to 104° F/0° C to 40° C
Storage/ Transportation Temperature	-40° F to 140° F/-40° C to 60° C
Operating Humidity	20% to 85% non-condensing
Storage Humidity	5% to 85% non-condensing
Firmware	

alone appilcations, connect to peripherals, and much more. ZPL and ZPL II - Zebra Programming Language provides sophisticated label formatting and printer control and is compatible with all Zebra printers. EPL and EPL2" — Eltron® Programming Language with Line Mode sImplifies label formatting and enables format compatibility with legacy applications. (EPi.

Electrical

Auto-detectable (PFC Compliant) 100-240VAC, 50-60Hz ENERGY STAR qualified

Options and Accessories

available on 203 dpl models only.)

RFID Field-installable on-metal RFID kit avallable (7T411) only, not available on the 600 dpi model) Connectivity Two open communication slots to add internal cards for: • Dual band 802.11ac Wi-Fi and Bluetooth Parallel (bl-directional Interface)
 10/100 Ethernet
 Applicator interface Rewind: Internally rewinds a full roll of printed labels on 3" core, or peels and rewinds liner (factory) Media Handling

- Installed only)
- · Peei: Front-mount, passive peel option
- Peel: Liner take-up additional full-roll liner take-up spir:dle accommodates standard printer bas
- . Cutter: Front-mount quillotine cutter and catch tray • 1 in. I.D. Core media supply hanger
- Ink-side in ribbon supply spIndle

Keyboard Display Unit - ZKDU" keyboard display units for stand-alone printing

The ZT400 Series RFID is ideal in:

Manufacturing

- Item-level tagging
- · Asset tagging
- Work-In-process
- serial numbers
- Packaging labeling
- · Receiving/put-

Transportation and Logistics

- · Order picking/ packing
- · Shipping/receiving
- · Cross-docking
- · Compliance labeling
- Pallet/asset tagging

Retail

- Back-of-store operations
- Item-level tagging
- · Distribution centers
- · Security tagging

Healthcare

- · Laboratory labeling
- · Specimen labeling
- · Pharmacy labeling
- · Asset management/ tagging

Fonts and Graphics

16 resident expandable ZPL II bitmap and two resident scalable ZPL fonts Asian and other international scalable and smooth bitmapped fonts $\frac{1}{2} \left(\frac{1}{2} \right) = \frac{1}{2} \left(\frac{1}{2} \right) \left(\frac{1}{2}$

ZT400 Series RFID Specifications (continued)

Unicode™: For multi-language printing Downloadable objects include graphics, scalable and bitmap fonts, label templates and formats $\,$ IBM Code Page 850 International character sets are available in the fonts A, B, C, D. F. F. G and 0 through software control Code Page 1250, 1252, 1253, 1254, 1255 Support with font D 64 MB user-available non-volatile memory storage for downloadable objects 8 MB user-available SDRAM **Barcode Symbologies** Linear Barcodes Code 11, Code 39, Code 93, Code 128 with subsets A/B/C and UCC Case Codes, ISBT-128, UPC-A, UPC-E, EAN-8, EAN13, UPC and EAN 2- or 5-digit extensions, Plessey, Postnet, Standard 2-of-5, Industrial 2-of-5, Interleaved 2-of-5, Logmars, MSI, Codabar, Planet Code Two Dimensional Codablock, PDF417, Code 49, DataMatrix, MaxiCode, QR Barcodes Code, TLC 39, MicroPDF, RSS-14 (and composite), Aztec **Agency Approvals** Safety IEC 60950, EN 55022 Class B, EN 55024, EN 61000-3-2, cTUVus, CE Marking, FCC-B, ICES-003, VCCI, C-Tick, **Emissions** NOM, S-Mark (Arg), CCC, CU, BSMI, KCC, SABS, IN-Metro **Print DNA Software Solutions Development Tools** With faster, easier and smarter integration of Zebra printers with your devices and applications, your

Zebra printing solutions are up and running in less

Print DNA Software Solutions (Continued)		
Management Tools	Minimize IT effort and maximize IT control with Print DNA management tools — the easy way to add and manage any number of printers, anywhere — from a handful of printers to thousands of printers all around the world.	
Productivity Tools	Reach new levels of productivity with innovations that streamline tasks and workflows, optimize device performance and solve tomorrow's printing problems today.	
Visibility Tools	Regardless of whether or not you have an existing Mobile Device Management solution in place, robust visibility tools provide unparalleled insight Into printer health, usage and performance.	
Product Warranty		
	ore warranted against defects in workmanship and f1 (one) year from the date of shipment.	
Recommended Se	rvices	
productivity of your decomprehensive coverage	al and Select Services maximize the availability and vices. Key features include 24/7 technical support, ge, advance replacement and software updates. is bility Services are available.	

Features are subject to availability. Specifications are subject to change without notice.





PRINT DNA SOFTWARE

This printer is supported by our powerful Print DNA suite of applications, utilities and developer tools that give our printers better performance, simplified remote manageability, and easier integration.



Print DNA features may vary by model and a Support Contract may be required. For more information, please visit:



